





STORAGE TANKS SPECS

STORAGE TANKS TECHNICAL DATA SPECIFICATIONS



STORAGE TANKS OPTIONS

*PRESSURE RATED 1 BAR/15PSI	<input type="checkbox"/>
JACKET	<input type="checkbox"/>
INSULATE	<input type="checkbox"/>
SHELL	<input type="checkbox"/>
LOAD CELLS	<input type="checkbox"/>
CIP	<input type="checkbox"/>
SITE GLASS STANDARD PLASTIC TUBE	<input type="checkbox"/>
**CASTERS STAINLESS STEEL NON MARING	<input type="checkbox"/>
SKID MOUNT WITH ACCESSORIES	<input type="checkbox"/>

MODEL	WORKING CAPACITY LITERS (GALLONS)	TOTAL CAPACITY LITERS (GALLONS)	EXTRA OVERHEAD PERCENTAGE	TANK DIMENSIONS					LOADS (KG)		LEGS	MANWAY Ø
				A	B	C (Ø)	D	E	EMPTY	LIVE		
ST-200	200 L (52.8 gal)	243.3 L (64.3 gal)	21.65	1.39 m 54.9 in	1.15 m 45.56 in	0.71 m 28 in	0.61 m 24 in	0.18m 7.375 in	89 Kg 196 lb	290 kg 639 lb	3	12 in
ST-500	500 L (132.29 gal)	603 L (159.5 gal)	20.6	1.85 m 73.06 in	1.53 m 60.5 in	0.914 m 36 in	0.914 m 36 in	0.184 m 7.25 in	129 Kg 284 lb	733 kg 1,616 lb	3	16 in
ST-1000	1000 L (264.5 gal)	1236 L (326.73 gal)	23.6	2.5 m 98.81 in	2.18 m 86 in	1.01 m 40 in	1.52 m 60 in	0.214 m 8.438 in	198 Kg 436 lb	1,435 kg 3163 lb	3	16 in
ST-1500	1500 L (396 gal)	1788 L (472 gal)	19.2	2.57 m 101.375 in	2.12 m 83.68 in	1.21 m 48 in	1.52 m 60 in	0.211 m 8.313 in	290 Kg 639 lb	2,078 kg 4,581 lb	4	18 in
ST-2000	2000 L (529 gal)	2355 L (622 gal)	17.8	2.6 m 102.5 in	2.13 m 84.12 in	1.39 m 55 in	1.52 m 60 in	0.211m 8.313 in	3,08Kg 679 lb	2,648 kg 5,837 lb	4	18 in
ST-2500	2500 L (660 gal)	3030 L (800 gal)	21.2	2.91 m 114.625 in	2.4 m 97 in	1.44 m 57 in	1.82 m 72 in	0.209 m 8.188 in	372 Kg 820 lb	3,402 kg 7,500 lb	4	18 in
ST-3000	3000 L (793 gal)	3,591 L (949 gal)	19.7	2.9 m 114.563 in	2.4 m 96.5 in	1.57 m 62 in	1.82 m 72 in	0.202 m 7.938 in	406 Kg 895 lb	3,997 kg 8,811 lb	4	18 in
ST-4000	4000 L (1,058 gal)	4,771 L (1,260 gal)	19.3	3.51 m 138.563 in	3 m 120.87 in	1.57 m 62 in	2.43 m 96 in	0.202 m 7.938 in	470 Kg 1,036 lb	5,240 kg 11,552 lb	5	18 in
ST-5000	5000 L (1,310 gal)	6,095 L (1,610 gal)	21.9	3.52 m 138.953 in	3 m 120.87 in	1.77 m 70 in	2.43 m 96 in	0.191 m 7.563 in	558 Kg 1,230 lb	6,652 kg 14,665 lb	5	18 in
ST-6000	6000 L (1,585.5 gal)	7005 L (1,850 gal)	16.8	3.54 m 139.5 in	3.1 m 122 in	1.88 m 74 in	2.43 m 96 in	0.211 m 8.313 in	571 Kg 1,258 lb	7,389 kg 16,289 lb	5	18 in
ST-8K	8000 L (2,113 gal)	9675 L (2556 gal)	21.5	3.56 m 140.5 in	3.1 m 125.68 in	2.2 m 88 in	2.43 m 96 in	0.214 m 8.438 in	702 kg 1,547 lb	10,377 kg 22,877 lb	5	18 in
ST-10K	10000 L (2,642 gal)	12614 L (3,332 gal)	26.1	4.16 m 163.81 in	3.8 m 150 in	2.4 m 90 in	2.43 m 120 in	0.214 m 8.438 in	828 kg 1,827 lb	13,444 kg 29,638 lb	5	18 in
ST-12.5K	12500 L (3,302 gal)	15,604 L (4,122 gal)	24.8	4.16 m 163.81 in	3.8 m 150.5 in	2.6 m 100 in	2.7 m 120 in	0.214 m 8.438 in	939 kg 2070 lb	16,543 kg 36470 lb	5	18 in
ST-15K	15000 L (3,963) gal)	18,569 L (4,905 gal)	23.8	4.2 m 165.688 in	3.8 m 152.12 in	2.75 in 109 in	3.05 m 120 in	0.214 m 8.438 in	1037 kg 2286 lb	19,591 kg 43,191 lb	5	18 in
ST-20K	20000 L (5,283) gal)	29,774 L (7,866 gal)	48.9	5.15m 202.82 in	4.6 m 180.25 in	2.8 m 126 in	3.6 m 144 in	0.23m 9.188in	2,003 Kg 4416 lb	31,778 kg 70,062 bl	5	24 in
ST-25K	25000 L (6,604) gal)	31,222.6 L (8,248 gal)	24.9	5.14 m 202.75 in	4.6 m 181.5 in	3.1 m 129 in	3.6 m 144 in	0.23m 9.188in	2,061 kg 4,543 lb	33,283 kg 73,376 lb	5	24 in
ST-30K	30000 L (7,925) gal)	36,515 L (9,646 gal)	21.7	6.05 m 238.5 in	5.5 m 216.87 in	3.4 m 125 in	3.6 m 180 in	0.23m 9.188in	1,897 Kg 4,181 lb	38,411 kg 84,681 lb	5	24 in
ST-35K	35000 L (9,246) gal)	42,642 L (11,265 gal)	21.8	6.07 m 239.12 in	5.5 m 218.37 in	3.6 m 135 in	3.6 m 180 in	0.23m 9.188in	2,545 kg 5,610 lb	45,186 kg 99,619 lb	6	24 in
ST-40K	40000 L (10,567) gal)	48,977 L (12,938 gal)	22.4	6.6 m 263.12 in	6.1 m 424.51 in	3.9 m 136 in	3.6 m 204 in	0.23m 9.188in	2,808 kg 6,190 in	51,785 kg 114,166 lb	6	24 in